

# Pharmsteri™ PES Cartridge Filter

*PSTS series filters provide economical filtration for pharmaceutical and food and beverage applications*

PSTS series cartridge filters join our portfolio of filtration solutions that help ensure reliable product processing. Constructed of polypropylene components and a hydrophilic polyethersulfone (PES) membrane, Pharmsteri™ cartridge filters are economical and efficient for use in various pharmaceutical and food and beverage applications.

Our portfolio of Pharmsteri™ PES filters is 100% tested during manufacturing to ensuring high quality for sterility assurance. Various fitting sizes and types are available to provide design flexibility and versatility in a broad range of applications.

## APPLICATIONS

### Pharmaceutical

- Bioburden reduction of LVP/SVP
- Sterile filtration for LVP/SVP/API
- Bulk chemicals

### Food and Beverage

- Facility water
- Bottled water
- Soft drinks

## FEATURES & BENEFITS

<b>Various fitting sizes and types available</b>	Fits most stainless-steel housings, providing design flexibility and versatility in a broad range of applications
<b>Optimized form factor</b>	Allows high flow and low pressure drop, lowering cost of ownership
<b>All components meet USP &lt;88&gt; Class VI Plastics Test</b>	Provides biosafety insurance and global regulatory compliance




*Allows high flow and low pressure drop, lowering cost of ownership.*

## SPECIFICATIONS


<b>Retention rating</b>	0.22, 0.45 µm	
<b>Materials</b>	Media	Polyethersulfone (PES)
	Support	Polypropylene
	Sleeve, core, top, and end caps	Polypropylene
	O-ring	Silicone
<b>Sealing technology</b>	Thermal bonding without adhesives	
<b>Filtration area</b>	≥0.6 m <sup>2</sup> /10" cartridge	
<b>Integrity test</b>	Minimum bubble point at 25°C (77°F)	≥3500 mbar
	Maximum diffusion flow at 2800 mbar at 25°C (77°F)	5" cartridge: ≤15 mL/min
		10" cartridge ≤30 mL/min
<b>Maximum operating conditions</b>	Maximum forward differential pressure	4.2 bar @ 25°C (77°F), 2.0 bar @ 80°C (176°F)
	Maximum operating temperature	80°C (176°F)
<b>Multiple sterilization cycles</b>	20 cycles of steam-in-place (SIP) sterilization or autoclave, 30 min at 127°C (261°F)	
<b>Endotoxin releasing</b>	<0.25 EU/mL as determined by the LAL test	
<b>TOC</b>	<0.5 mg/L after a water flush of 11 L/10" cartridge	
<b>Conductivity</b>	≤1.3 µS/cm after water flush of 11 L/10" cartridge	
<b>Particle release</b>	Meets the requirements of WFI set by USP	
<b>NVR</b>	After autoclaving and 24-hours in 50% ethanol water with vibration (contact Entegris for details)	
<b>Material toxicity</b>	All components meet the requirements of the USP <88> Reactivity Test for Class VI Plastics	
<b>Bacterial challenge test</b>	Passed the bacterial challenge test using Brevundimonas diminuta (ATCC 19146) at a minimum challenge concentration 1x10 <sup>7</sup> CFU/cm <sup>2</sup> (0.22 µm)	
<b>Indirect food additive</b>	Meets the FDA Indirect Food Additive requirements cited in 21 CFR 177-182	
<b>Food contact material</b>	(EU) No. 1935/2004, (EU) No. 10/2011	
<b>Quality</b>	Manufactured in accordance with ISO 9001 and ISO 13485 certified quality management system	

## PERFORMANCE DATA




## DIMENSIONS

Code 0



Length	Code 0 Dimension A
5"	148.0 mm (5.8")
10"	273.0 mm (10.7")
20"	517.5 mm (20.4")
30"	762.0 mm (30.0")
40"	1006.5 mm (39.6")


Code 5



Length	Code 5 Dimension A
5"	—
10"	314.0 mm (12.4")
20"	558.5 mm (22.0")
30"	803.0 mm (31.6")
40"	1047.5 mm (41.2")


## DIMENSIONS

Code 6



Length	Code 6 Dimension A
5"	150.5 mm (5.9")
10"	276.0 mm (10.9")
20"	520.0 mm (20.5")
30"	764.5 mm (30.1")
40"	1009.0 mm (39.7")

Code 7



Length	Code 7 Dimension A
5"	–
10"	316.5 mm (12.5")
20"	561.0 mm (22.1")
30"	805.5 mm (31.7")
40"	1050.0 mm (41.3")

## ORDERING INFORMATION

PART NUMBER	CONNECTION	LENGTH	O-RING	RETENTION RATING
PSTS022005S1	Code 0	5"	Silicone	0.22 µm
PSTS022010S1	Code 0	10"	Silicone	0.22 µm
PSTS022020S1	Code 0	20"	Silicone	0.22 µm
PSTS022030S1	Code 0	30"	Silicone	0.22 µm
PSTS022040S1	Code 0	40"	Silicone	0.22 µm
PSTS022510S1	Code 5	10"	Silicone	0.22 µm

## ORDERING INFORMATION

PART NUMBER	CONNECTION	LENGTH	O-RING	RETENTION RATING
PSTS022520S1	Code 5	20"	Silicone	0.22 µm
PSTS022530S1	Code 5	30"	Silicone	0.22 µm
PSTS022540S1	Code 5	40"	Silicone	0.22 µm
PSTS022605S1	Code 6	5"	Silicone	0.22 µm
PSTS022610S1	Code 6	10"	Silicone	0.22 µm
PSTS022620S1	Code 6	20"	Silicone	0.22 µm
PSTS022630S1	Code 6	30"	Silicone	0.22 µm
PSTS022640S1	Code 6	40"	Silicone	0.22 µm
PSTS022710S1	Code 7	10"	Silicone	0.22 µm
PSTS022720S1	Code 7	20"	Silicone	0.22 µm
PSTS022730S1	Code 7	30"	Silicone	0.22 µm
PSTS022740S1	Code 7	40"	Silicone	0.22 µm
PSTS045005S1	Code 0	5"	Silicone	0.45 µm
PSTS045010S1	Code 0	10"	Silicone	0.45 µm
PSTS045020S1	Code 0	20"	Silicone	0.45 µm
PSTS045030S1	Code 0	30"	Silicone	0.45 µm
PSTS045040S1	Code 0	40"	Silicone	0.45 µm
PSTS045510S1	Code 5	10"	Silicone	0.45 µm
PSTS045520S1	Code 5	20"	Silicone	0.45 µm
PSTS045530S1	Code 5	30"	Silicone	0.45 µm
PSTS045540S1	Code 5	40"	Silicone	0.45 µm
PSTS045605S1	Code 6	5"	Silicone	0.45 µm
PSTS045610S1	Code 6	10"	Silicone	0.45 µm
PSTS045620S1	Code 6	20"	Silicone	0.45 µm
PSTS045630S1	Code 6	30"	Silicone	0.45 µm
PSTS045640S1	Code 6	40"	Silicone	0.45 µm

## ORDERING INFORMATION

PART NUMBER	CONNECTION	LENGTH	O-RING	RETENTION RATING
PSTS045710S1	Code 7	10"	Silicone	0.45 µm
PSTS045720S1	Code 7	20"	Silicone	0.45 µm
PSTS045730S1	Code 7	30"	Silicone	0.45 µm
PSTS045740S1	Code 7	40"	Silicone	0.45 µm

### FOR MORE INFORMATION

Please call your Regional Customer Service Center today to learn what Entegris can do for you. Visit [entegris.com](https://www.entegris.com) and select the [Contact Us](#) link to find the customer service center nearest you.

### TERMS AND CONDITIONS OF SALE

All purchases are subject to Entegris' Terms and Conditions of Sale. To view and print this information, visit [entegris.com](https://www.entegris.com) and select the [Terms & Conditions](#) link in the footer.



Corporate Headquarters  
129 Concord  
Billerica, MA 01821  
USA

Customer Service  
Tel +1 952 556 4181  
Fax +1 952 556 8022  
Toll Free 800 394 4083

Entegris®, the Entegris Rings Design®, and other product names are trademarks of Entegris, Inc. as listed on [entegris.com/trademarks](https://www.entegris.com/trademarks). All third-party product names, logos, and company names are trademarks or registered trademarks of their respective owners. Use of them does not imply any affiliation, sponsorship, or endorsement by the trademark owner.

©2021-2022 Entegris, Inc. | All rights reserved. | Printed in the USA | 9000-11843ENT-0422